



**DESCRIPTION**

The NSL-5522 is a light dependent resistor with sensitivity in the visible light region. The CdS photoconductive cell is on a TO-5 ceramic and the photocell surface is plastic encapsulated for moisture resistance.

**FEATURES**

- Passive resistance output
- Ceramic package

**RELIABILITY**

Contact Luna for recommendations on specific test conditions and procedures.

**APPLICATIONS**

- Industrial

**ABSOLUTE MAXIMUM RATINGS**

SYMBOL	MIN		MAX	UNITS	
Voltage (peak AC or DC)	-	-	120	V	T <sub>a</sub> = 23°C UNLESS OTHERWISE NOTED
Power Dissipation @ 25°C	-	-	125	mw	Derate linearly to 0 at 75°C
Operating Temperature	-60	to	+75	°C	Non condensing
Storage Temperature	-60	to	+75	°C	-
Soldering Temperature	-	-	+260	°C	>2 mm from case for < 10 sec.

**OPTO-ELECTRICAL PARAMETERS**

T<sub>a</sub> = 23°C UNLESS NOTED OTHERWISE

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Light Resistance	1 ftc., 2854°K <sup>1</sup>	11	19	26	KΩ
	100 ftc., 2854°K <sup>1</sup>	-	400	-	KΩ
Dark Resistance	5 sec after removal of test light	15	-	-	MΩ
Spectral Peak	-	-	550	-	nm

**NOTE:**

1. Cell lights adapted at 30 to 50 Ftc for 16 hrs minimum prior to electrical tests